

Nature-inspired Coordination for Complex Distributed Systems

Andrea Omicini
andrea.omicini@unibo.it

Dipartimento di Informatica: Scienza e Ingegneria (DISI)
ALMA MATER STUDIORUM—Università di Bologna

IDC 2012
Intelligent Distributed Computing
Calabria, Italy – 26th of September 2012



1 Why?

2 Examples

- Early
- Modern
- Issues

3 Tuples

4 Trends



Outline

1 Why?

- ## 2 Examples
- Early
 - Modern
 - Issues

3 Tuples

4 Trends



Why Nature-inspired Models?

Complex natural systems

- such as physical, chemical, biochemical, biological, social systems
- natural system exhibit *features*
 - such as distribution, openness, situation, fault tolerance, robustness, adaptiveness, . . .
- which we would like to understand, capture, then bring to *computational* systems

Nature-Inspired Computing (NIC)

- For instance, NIC [Liu and Tsui, 2006] summarises decades of research activities
- putting emphasis on *autonomy* of components, and on *self-organisation* of systems

Why Coordination Models?

Interaction

- most of the complexity of complex computational systems comes from interaction [Omicini et al., 2006]
- along with an essential part of their expressive power [Wegner, 1997]

Coordination

- since coordination is essentially the science of managing the space of interaction [Wegner, 1997]
- coordination models and languages [Ciancarini, 1996] provide abstractions and technologies for the engineering of complex computational systems [Ciancarini et al., 2000]



Why Nature-inspired Coordination?

Coordination issues in natural systems

- coordination issues did not first emerge in computational systems
- [Grassé, 1959] noted that in termite societies *“The coordination of tasks and the regulation of constructions are not directly dependent from the workers, but from constructions themselves.”*

Coordination as the key issue

- many well-known examples of natural systems – and, more generally, of complex systems – seemingly rely on simple yet powerful coordination mechanisms for their key features—such as self-organisation
- it makes sense to focus on nature-inspired coordination models as the core of complex nature-inspired computational systems

Outline

1 Why?

2 **Examples**

- Early
- Modern
- Issues

3 Tuples

4 Trends



Stigmergy I

Stigmergy in insect societies

- nature-inspired models of coordination are grounded in studies on the behaviour of social insects, like ants or termites
- [Grassé, 1959] introduced the notion of **stigmergy** as the fundamental coordination mechanism in termite societies
- in ant colonies, pheromones act as environment markers for specific social activities, and drive both the *individual* and the *social* behaviour of ants



Stigmergy II

Stigmergy in computational systems

- nowadays, stigmergy generally refers to a set of nature-inspired coordination mechanisms mediated by the *environment*
- *digital pheromones* [Parunak et al., 2002] and other *signs* made and sensed in a shared environment [Parunak, 2006] can be exploited for the engineering of adaptive and self-organising computational systems



Chemical Coordination

Chemical reactions as (natural) coordination laws

- inspiration comes from the idea that complex physical phenomena are driven by the (relatively) simple chemical reactions
- coordinating the behaviours of a huge amount of components, as well as the global system evolution

Chemical reactions as (computational) coordination laws

- Gamma [Banâtre and Le Métayer, 1990] is a *chemistry-inspired coordination* model—as for the CHAM (chemical abstract machine) model [Berry, 1992]
- coordination in Gamma is conceived as the evolution of a space governed by chemical-like rules, globally working as a rewriting system [Banâtre et al., 2001]

Field-based Coordination

Computational fields as coordination laws

- field-based coordination models like TOTA [Mamei and Zambonelli, 2004] are inspired by the way masses and particles move and self-organise according to gravitational/electromagnetic fields [Mamei and Zambonelli, 2006]
- there, computational force fields, generated either by the active components or by the pervasive coordination infrastructure, propagate across the environment, and drive the actions and motion of the component themselves



(Bio)chemical Coordination

Chemical reactions as coordination laws

- chemical tuple spaces [Viroli et al., 2010] exploit the chemical metaphor at its full extent—beyond Gamma
- data, devices, and software agents are represented in terms of chemical reactants, and system behaviour is expressed by means of chemical-like laws
- which are actually time-dependent and stochastic
- embedded within the coordination medium
- biochemical tuple spaces [Viroli and Casadei, 2009] add *compartments*, *diffusion*, and *stochastic behaviour* of coordination primitives



Basic Issues of Nature-inspired Coordination I

Environment

- environment is essential in nature-inspired coordination
 - it works as a **mediator** for component interaction — through which the components of a distributed system can communicate and coordinate indirectly
 - it is **active** — featuring autonomous dynamics, and affecting component coordination
 - it has a **structure** — requiring a notion of *locality*, and allowing components of any sort to *move* through a **topology**



Basic Issues of Nature-inspired Coordination II

Stochastic behaviour

- complex systems typically require probabilistic models
 - *don't know / don't care* non-deterministic mechanisms are not expressive enough to capture all the properties of complex systems such as biochemical and social systems
 - probabilistic mechanisms are required to fully capture the dynamics of coordination in nature-inspired systems
 - coordination models should feature (possibly simple yet) expressive mechanisms to provide coordinated systems with stochastic behaviours



Outline

- 1 Why?
- 2 Examples
 - Early
 - Modern
 - Issues
- 3 Tuples**
- 4 Trends



The Ancestor

LINDA [Gelernter, 1985]

- LINDA is the ancestor of all tuple-based coordination models [Rossi et al., 2001]
- in LINDA, coordinables synchronise, cooperate, compete
 - based on tuples
 - available in the tuple spaces, working as the coordination media
 - by *associatively* accessing, consuming and producing tuples
- the same holds for any tuple-based coordination model



LINDA is *not* a Nature-inspired Model

So, *why* LINDA?

Why tuple-based models???



Why Tuple-based Models? I

Expressiveness

- LINDA is a sort of *core* coordination model
- making it easy to face and solve many typical problems of complex distributed systems
- *complex* coordination problems are solved with *few, simple* primitives
- whatever the model used to measure *expressiveness* of coordination, tuple-based languages are highly-expressive [Busi et al., 1998]



Why Tuple-based Models? II

Environment-based coordination

- generative communication [Gelernter, 1985] requires *permanent* coordination abstractions
- so, tuple spaces are provided as *coordination services* by the *coordination infrastructure* [Viroli and Omicini, 2006]
- they can be interpreted as *coordination artefacts* shaping computational *environment* [Omicini et al., 2004]
- as such, they can be exploited to support *environment-based* coordination [Ricci et al., 2005]



Why Tuple-based Models? III

Extensibility

- whatever its expressiveness, LINDA was conceived as a coordination model for closed, parallel systems
- so, in fact, some relevant problems of today open, concurrent systems cannot be easily solved with LINDA either in practice or in theory
- as a result, tuple-based models have been extended with new simple yet powerful mechanisms
- generating a plethora of tuple-based coordination models
[Rossi et al., 2001]



Why Tuple-based Models? IV

Nature-inspired extensions

- LINDA may *not* be nature-inspired, but many of its extensions *are*
- many of the coordination models depicted before
 - stigmergy [Parunak, 2006]
 - field-based [Mamei and Zambonelli, 2004]
 - chemical [Viroli et al., 2010] and biochemical [Viroli and Casadei, 2009]
- along with many others, such as
 - cognitive stigmergy [Ricci et al., 2007]
 - pervasive ecosystems [Viroli et al., 2012]
- are actually nature-inspired tuple-based coordination models



Toward Self-organising Coordination I

Just *some* is not enough

- capturing just *some* of the principles and mechanisms of natural systems does not ensure to capture their *essence*
- for instance, chemical coordination models such as Gamma and CHAM exploit the raw schema of computation as chemical reaction, but are *not* expressive enough to fully reproduce any non-trivial chemical system
- in fact, *e.g.*, even the simplest model for real chemical reactions requires a notion of *reaction rate*
- neither Gamma nor CHAM provide for such a notion, they are not expressive enough to fully match the behaviour of real chemical systems



Toward Self-organising Coordination II

Self-organising coordination [Viroli et al., 2009]

- most of the traditional coordination models feature abstractions enacting coordination laws that are typically *reactive*, (mostly) *deterministic*, and *global* as well
- in complex systems featuring self-* properties, instead, coordination patterns typically appear at the global level by *emergence*, from *probabilistic*, *time-dependent* coordination laws based on *local* criteria
- in particular, many coordination models either implicitly or explicitly recognise that full expressiveness requires addressing the issues of time dependency and stochasticity



Examples I

STOKLAIM

- STOKLAIM [De Nicola et al., 2006] – a *stochastic* extension of the LINDA-derived KLAIM model for mobile coordination [De Nicola et al., 1998] – adds distribution rates to coordination primitives—thus making it possible the modelling of non-deterministic real-life phenomena such as failure rates and inter-arrival times

SwarmLinda

- SwarmLinda [Tolksdorf and Menezes, 2004] enhances LINDA implementation with swarm intelligence to achieve features such as scalability, adaptiveness, and fault-tolerance—by modelling tuple templates as ants, featuring probabilistic behaviour when looking for matching tuples in a distributed setting

Examples II

Time-aware ReSpecT

- ReSpecT [Omicini and Denti, 2001] generally addresses *time dependency* by capturing time events and supporting the definition and enforcement of *timed coordination policies* [Omicini et al., 2005]—so, ReSpecT-programmed tuple centres can work as time-dependent abstractions for the coordination of distributed processes [Omicini et al., 2007]



Enough?

No.

- in the overall, the above-mentioned models *fail* to capture all the essential features of nature-inspired coordination
- this is why many novel research lines stretch existing tuple-based models to achieve the expressive power required to model and build distributed systems with a complexity comparable to natural systems [Omicini and Viroli, 2011]



Outline

- 1 Why?
- 2 Examples
 - Early
 - Modern
 - Issues
- 3 Tuples
- 4 Trends



Full Dynamics

Expressing the *full dynamics* of complex natural systems

- for instance, Gamma mimics chemical reactions, but does not capture essential issues in chemical processes such as reaction rates and concentration [Banâtre and Le Métayer, 1990, Banâtre et al., 2001]
- instead, *(bio)chemical tuple spaces* fully exploit the chemical metaphor by providing time-dependent and stochastic chemical laws [Viroli et al., 2010, Viroli and Casadei, 2009]
- more generally, the goal is to allow coordinated systems to express the full dynamics of complex natural systems



Blending Metaphors

Mixing abstractions & mechanisms from different conceptual sources

- for instance, the SAPERE coordination model for pervasive service ecosystems [Zambonelli et al., 2011, Viroli et al., 2012] exploits
 - the *chemical* metaphor for driving the evolution of coordination abstractions
 - *biochemical* abstractions for topology and diffusion
 - the notion of *ecosystem* in order to model the overall system structure and dynamics
- this mostly resembles natural systems, when they are observed in their whole complexity, crossing their many layers



Knowledge-oriented Coordination

Integrating nature-inspired with knowledge-oriented coordination

- intelligent distributed systems in knowledge intensive environments, as well as complex socio-technical systems, require automatic understanding of data and information
- knowledge-oriented coordination [Nardini et al.,] exploits coordination abstractions capable of semantic interpretation
- for instance
 - both chemical tuple spaces and SAPERE abstractions rely on the semantic interpretation of coordination items—in the same way as *semantic tuple centres* [Nardini et al., 2011]
 - MoK (Molecules of Knowledge) is a a nature-inspired coordination model focussing on knowledge management [Mariani and Omicini, 2012], exploiting the full power of the biochemical metaphor to achieve *knowledge self-organisation* within knowledge-intensive environments

Core Mechanisms

Understanding the basic elements of expressiveness

- LINDA is a glaring example of a minimal set of coordination mechanisms providing a wide range of coordination behaviours
- the goal is understanding the minimal set of coordination primitives required to design complex stochastic behaviours
- for instance, *uniform coordination primitives* – that is, LINDA-like coordination primitives returning tuples matching a template with a uniform distribution [Gardelli et al., 2007] – seemingly capture the full-fledged dynamics of real chemical systems within the coordination abstractions



Predicting Complex Behaviours

Engineering unpredictable systems around predictable abstractions

- coordination models and technologies are typically in charge of harnessing the complexity of articulated computational systems [Ciancarini et al., 2000]
- coordination abstractions are often at the core of complex systems
- while this does not make complex system generally predictable, it makes it possible in principle to make them *partially predictable*, based on the predictability of the core coordinative behaviour
- suitably-formalised coordination abstractions, along with a suitably-defined engineering methodology, could in principle ensure the predictability of given system properties within generally-unpredictable coordinated systems—such as nature-inspired systems



Conclusion I

History and evolution

- starting from early chemical and stigmergic approaches, nature-inspired models of coordination evolved to become the *core of complex distributed systems*—such as pervasive, knowledge-intensive, intelligent, and self-* systems
- in this talk we shortly surveyed their history, devise their main issues, and point out the most promising trends
- focussing in particular on tuple-based coordination models



Conclusion II

In the overall. . .

- nature-inspired models of coordination already have a long history behind them
- and apparently a huge *potential* for development still to be explored
- to provide core abstractions and technologies for the engineering of complex computational systems



Thanks to...

- ... everybody here for listening, despite yesterday night
- ... Giancarlo Fortino for inviting me
- ... the SAPERE Project for the support ¹

¹This work has been supported by the EU-FP7-FET Proactive project SAPERE *Self-aware Pervasive Service Ecosystems*, under contract no. 256873.



Bibliography I



Banâtre, J.-P., Fradet, P., and Le Métayer, D. (2001).
Gamma and the chemical reaction model: Fifteen years after.
In Calude, C. S., Păun, G., Rozenberg, G., and Salomaa, A., editors, *Multiset Processing. Mathematical, Computer Science, and Molecular Computing Points of View*, volume 2235 of *LNCS*, pages 17–44. Springer.



Banâtre, J.-P. and Le Métayer, D. (1990).
The GAMMA model and its discipline of programming.
Science of Computer Programming, 15(1):55–77.



Berry, G. (1992).
The chemical abstract machine.
Theoretical Computer Science, 96(1):217–248.



Busi, N., Gorrieri, R., and Zavattaro, G. (1998).
A process algebraic view of Linda coordination primitives.
Theoretical Computer Science, 192(2):167–199.



Ciancarini, P. (1996).
Coordination models and languages as software integrators.
ACM Computing Surveys, 28(2):300–302.



Bibliography II



Ciancarini, P., Omicini, A., and Zambonelli, F. (2000).
Multiagent system engineering: The coordination viewpoint.
In Jennings, N. R. and Lespérance, Y., editors, *Intelligent Agents VI. Agent Theories, Architectures, and Languages*, volume 1757 of *LNAI*, pages 250–259. Springer.
6th International Workshop (ATAL'99), Orlando, FL, USA, 15–17 July 1999. Proceedings.



De Nicola, R., Ferrari, G., and Pugliese, R. (1998).
KLAIM: A kernel language for agent interaction and mobility.
IEEE Transaction on Software Engineering, 24(5):315–330.



De Nicola, R., Latella, D., Katoen, J.-P., and Massink, M. (2006).
StoKlaim: A stochastic extension of Klaim.
Technical Report 2006-TR-01, Istituto di Scienza e Tecnologie dell'Informazione
“Alessandro Faedo” (ISTI).



Gardelli, L., Viroli, M., Casadei, M., and Omicini, A. (2007).
Designing self-organising MAS environments: The collective sort case.
In Weyns, D., Parunak, H. V. D., and Michel, F., editors, *Environments for MultiAgent Systems III*, volume 4389 of *LNAI*, pages 254–271. Springer.
3rd International Workshop (E4MAS 2006), Hakodate, Japan, 8 May 2006. Selected
Revised and Invited Papers.



Bibliography III



Gelernter, D. (1985).
Generative communication in Linda.
ACM Transactions on Programming Languages and Systems, 7(1):80–112.



Grassé, P.-P. (1959).
La reconstruction du nid et les coordinations interindividuelles chez *Bellicositermes natalensis* et *Cubitermes* sp. la théorie de la stigmergie: Essai d'interprétation du comportement des termites constructeurs.
Insectes Sociaux, 6(1):41–80.



Liu, J. and Tsui, K. C. (2006).
Toward nature-inspired computing.
Communications of the ACM, 49(10):59–64.



Mamei, M. and Zambonelli, F. (2004).
Programming pervasive and mobile computing applications with the TOTA middleware.
In *Pervasive Computing and Communications*, pages 263–273.
2nd IEEE Annual Conference (PerCom 2004), Orlando, FL, USA, 14–17 March 2004.
Proceedings.



Bibliography IV



Mamei, M. and Zambonelli, F. (2006).
Field-Based Coordination for Pervasive Multiagent Systems. Models, Technologies, and Applications.
Springer Series in Agent Technology. Springer.



Mariani, S. and Omicini, A. (2012).
Molecules of knowledge: Self-organisation in knowledge-intensive environments.
In *Intelligent Distributed Computing VI*, pages 17–22. Springer, Calabria, Italy.
6th International Symposium on Intelligent Distributed Computing (IDC 2012).



Nardini, E., Omicini, A., and Viroli, M.
Semantic tuple centres.
Science of Computer Programming.
Special Issue on Self-Organizing Coordination. To appear.



Nardini, E., Omicini, A., Viroli, M., and Schumacher, M. I. (2011).
Coordinating e-health systems with TuCSon semantic tuple centres.
Applied Computing Review, 11(2):43–52.



Omicini, A. and Denti, E. (2001).
From tuple spaces to tuple centres.
Science of Computer Programming, 41(3):277–294.



Bibliography V



Omicini, A., Ricci, A., and Viroli, M. (2005).

Time-aware coordination in ReSpecT.

In Jacquet, J.-M. and Picco, G. P., editors, *Coordination Models and Languages*, volume 3454 of *LNCS*, pages 268–282. Springer-Verlag.

7th International Conference (COORDINATION 2005), Namur, Belgium, 20–23 April 2005. Proceedings.



Omicini, A., Ricci, A., and Viroli, M. (2006).

The multidisciplinary patterns of interaction from sciences to Computer Science.

In Goldin, D. Q., Smolka, S. A., and Wegner, P., editors, *Interactive Computation: The New Paradigm*, pages 395–414. Springer.



Omicini, A., Ricci, A., and Viroli, M. (2007).

Timed environment for Web agents.

Web Intelligence and Agent Systems, 5(2):161–175.



Omicini, A., Ricci, A., Viroli, M., Castelfranchi, C., and Tummolini, L. (2004).

Coordination artifacts: Environment-based coordination for intelligent agents.

In Jennings, N. R., Sierra, C., Sonenberg, L., and Tambe, M., editors, *3rd international Joint Conference on Autonomous Agents and Multiagent Systems (AAMAS 2004)*, volume 1, pages 286–293, New York, USA. ACM.



Bibliography VI



Omicini, A. and Viroli, M. (2011).
Coordination models and languages: From parallel computing to self-organisation.
The Knowledge Engineering Review, 26(1):53–59.



Parunak, H. V. D. (2006).
A survey of environments and mechanisms for human-human stigmergy.
In Weyns, D., Parunak, H. V. D., and Michel, F., editors, *Environments for Multi-Agent Systems II*, volume 3830 of *LNCS*, pages 163–186. Springer.



Parunak, H. V. D., Brueckner, S., and Sauter, J. (2002).
Digital pheromone mechanisms for coordination of unmanned vehicles.
In Castelfranchi, C. and Johnson, W. L., editors, *1st International Joint Conference on Autonomous Agents and Multiagent systems*, volume 1, pages 449–450, New York, NY, USA. ACM.



Ricci, A., Omicini, A., Viroli, M., Gardelli, L., and Oliva, E. (2007).
Cognitive stigmergy: Towards a framework based on agents and artifacts.
In Weyns, D., Parunak, H. V. D., and Michel, F., editors, *Environments for MultiAgent Systems III*, volume 4389 of *LNCS*, pages 124–140. Springer.
3rd International Workshop (E4MAS 2006), Hakodate, Japan, 8 May 2006. Selected Revised and Invited Papers.



Bibliography VII



Ricci, A., Viroli, M., and Omicini, A. (2005).
Environment-based coordination through coordination artifacts.
In Weyns, D., Parunak, H. V. D., and Michel, F., editors, *Environments for Multi-Agent Systems*, volume 3374 of *LNAI*, pages 190–214. Springer.
1st International Workshop (E4MAS 2004), New York, NY, USA, 19 July 2004. Revised Selected Papers.



Rossi, D., Cabri, G., and Denti, E. (2001).
Tuple-based technologies for coordination.
In Omicini, A., Zambonelli, F., Klusch, M., and Tolksdorf, R., editors, *Coordination of Internet Agents: Models, Technologies, and Applications*, chapter 4, pages 83–109. Springer.



Tolksdorf, R. and Menezes, R. (2004).
Using Swarm Intelligence in Linda Systems.
In Omicini, A., Petta, P., and Pitt, J., editors, *Engineering Societies in the Agents World IV*, volume 3071 of *LNCS*, pages 49–65. Springer.
4th International Workshops (ESAW 2003), London, UK, 29-31 October 2003. Revised Selected and Invited Papers.



Bibliography VIII



Viroli, M. and Casadei, M. (2009).

Biochemical tuple spaces for self-organising coordination.

In Field, J. and Vasconcelos, V. T., editors, *Coordination Languages and Models*, volume 5521 of *LNCS*, pages 143–162. Springer, Lisbon, Portugal.

11th International Conference (COORDINATION 2009), Lisbon, Portugal, June 2009. Proceedings.



Viroli, M., Casadei, M., Nardini, E., and Omicini, A. (2010).

Towards a chemical-inspired infrastructure for self-* pervasive applications.

In Weyns, D., Malek, S., de Lemos, R., and Andersson, J., editors, *Self-Organizing Architectures*, volume 6090 of *LNCS*, chapter 8, pages 152–176. Springer.

1st International Workshop on Self-Organizing Architectures (SOAR 2009), Cambridge, UK, 14-17 September 2009, Revised Selected and Invited Papers.



Viroli, M., Casadei, M., and Omicini, A. (2009).

A framework for modelling and implementing self-organising coordination.

In Shin, S. Y., Ossowski, S., Menezes, R., and Viroli, M., editors, *24th Annual ACM Symposium on Applied Computing (SAC 2009)*, volume III, pages 1353–1360, Honolulu, Hawai'i, USA. ACM.



Bibliography IX



Viroli, M. and Omicini, A. (2006).
Coordination as a service.
Fundamenta Informaticae, 73(4):507–534.
Special Issue: Best papers of FOCLASA 2002.



Viroli, M., Pianini, D., Montagna, S., and Stevenson, G. (2012).
Pervasive ecosystems: a coordination model based on semantic chemistry.
In Ossowski, S., Lecca, P., Hung, C.-C., and Hong, J., editors, *27th Annual ACM Symposium on Applied Computing (SAC 2012)*, Riva del Garda, TN, Italy. ACM.



Wegner, P. (1997).
Why interaction is more powerful than algorithms.
Communications of the ACM, 40(5):80–91.



Zambonelli, F., Castelli, G., Ferrari, L., Mamei, M., Rosi, A., Di Marzo, G., Risoldi, M., Tchao, A.-E., Dobson, S., Stevenson, G., Ye, Y., Nardini, E., Omicini, A., Montagna, S., Viroli, M., Ferscha, A., Maschek, S., and Wally, B. (2011).
Self-aware pervasive service ecosystems.
Procedia Computer Science, 7:197–199.
Proceedings of the 2nd European Future Technologies Conference and Exhibition 2011 (FET 11).



URLs I

Slides

- On APICe

`http://apice.unibo.it/xwiki/bin/view/Talks/
InvitedIdc2012`

- On SlideShare

`http://www.slideshare.net/andreaomicini/
natureinspired-coordination-for-complex-distributed-systems`



URLs II

Article

- On APICe

```
http://apice.unibo.it/xwiki/bin/view/Publications/  
NatureinspcoordIdc2012
```

- On SpringerLink

```
http://www.springerlink.com/content/  
43tmmn1j4t5616q8
```



Nature-inspired Coordination for Complex Distributed Systems

Andrea Omicini
andrea.omicini@unibo.it

Dipartimento di Informatica: Scienza e Ingegneria (DISI)
ALMA MATER STUDIORUM—Università di Bologna

IDC 2012
Intelligent Distributed Computing
Calabria, Italy – 26th of September 2012

